

INCRA PRODUCT OVERVIEW

		water repellents										densifiers & curing				damp proofing			easy-to-clean sealers				cleaner	
product-code		INCRASIL 401C *)	INCRASIL 421	INCRASIL 441	INCRASIL FS15	INCRACREAM FC25	INCRACREAM FC40	INCRACAT FT41	INCRASIL CW10	INCRASIL CW50	INCRASIL CW70	INCRACREAM CW80	INCRADENS HF30	INCRADENS HF40	INCRADENS HF80	INCRACURE IC18	INCRADAMP DP25	INCRADAMP DP50	INCRAGEL DP80	INCRASEAL EF10 *)	INCRASEAL EF40	INCRASEAL EF60	INCRASEAL EC90	INCRACLEAN AS11
substrate	masonry	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	concrete	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	natural stone	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	glass/carcoating/textile																							
ex/in	exterior	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	walls	walls	walls	•	•
	interior								•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
w/f	walls	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	floors										•	•	•	•	•	•	•	•	•	interior	interior	interior	•	•
treatm.	surface	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	admixture										•													
features	water-repellent	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	oil/fat-repellent												•	•	•	•				•	•	•	•	•
	damp proofing																•	•	•					
	hardening / densifying												•	•	•	•	•	•	•					
	photocatalytic/selfcleaning												•											
	damp permeable	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
base / active compounds	VOC-free	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	solvent: water	•	•	•		•	•	•		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	solvent: aliphatic hydrocarbon				•	•	•																	
	cream/gel					•	•					•							•					
	silane/siloxane	•	•	•	•	•	•	•	•	•	•	•						•	•	•	•	•	•	•
	fluoropolymer													•	•					•	•	•	•	•
	titaniumoxide							•												•	•	•	•	•
	acrylate															•								
miscellaneous	polysilicate												•	•	•		•			•	•	•		
	potassium/sodiumsilicate																•							
	siliconate																•							
	% active compound	51%	2,6%	1,3%	7%	25%	40%	20%	96%	10%	30%	80%	10%	6%	3%	18%	12%	10%	80%	31%	8%	5%	1,5%	11%
	highly active		•						•					•							•		•	
application	2 components							•																
	evt. combination with **) maintenance							EC90					EF60		•	•				•	•	HF30	FT41	
	facade-cleaner																							•
	flooding		•	•	•				•				•	•	•					•	•	•		•
	airless-spray		•	•	•				•				•	•	•	•				•	•	•	•	•
packaging	paint-roller					•	•	•	•	•		•	•	•	•					•	•	•	•	•
	brush					•	•	•				•												
	injection																•	•	•					
	admixture into concrete										•													
	600 ml cartridge											0,54 kg							0,54 kg					
	5 ltr can																			•				
	10 ltr can																•	•						•
	15 ltr bucket					12,7 kg	12,9 kg					13,5 kg							13,5 kg					
	25 ltr can		•	•	•				•	•	•		25 kg	•	•		•	•				•	•	•
	25 ltr can + 1 ltr bidon								•															
200 ltr drum		•	•	•				•	•	•		220 kg	•	•	•	•	•		•		•	•	•	
200 ltr drum open top					170 kg	172 kg					180 kg							180 kg						
500 ltr IBC	•																		•					
1.000 ltr IBC	•	•	•	•	850 kg	860kg						1100 kg		•	•	•	•						•	

*) concentrated product has to be diluted in water before use.

**) add 2-3% to clear cleaning water.

At every substrate always carry out a suitability test on a test area.

See for more detailed information and application-rules the Product Data Sheet (PDS) of the relating product.