

# INCRASURF V60

## PU-additives

# INCRA®

INCRASURF is a group of special PU-additives. These agents have unique properties to help in processing of PU-foam production. At the indicated use-levels they give also improved improved product characteristics.

### INCRASURF V60

INCRASURF V60 is a silicone based surfactant mixture that can be used to improve cell structure. It is used as additive on the line in a concentration of 2-4%. Can also be used as modifier in polyester polyol production at use levels of 3-6%.

### FEATURES & BENEFITS

INCRASURF V60 is used in PUR and PIR systems blown with pentane and new blowing agents to make fine celled foams. the product is used at 2-4% levels to give most effect.

### APPLICATION

INCRASURF V60 is used in combination with a standard silicone surfactant in rigid polyurethane foam to give better cell-structure.

### PRODUCT PROPERTIES

contains	mix of polymers, silicone surfactants and additives
components	1
appearance	viscous fluid
colour	clear colourless
spec. weight	ca. 1,05-1,10 g/cm <sup>3</sup> at +20° C
viscosity	ca.350 cps dynamic at +20°
flash point	> 200° C
condition	liquid
storage	store in closed original packaging above +5° C, protect against sun, frost and extreme temperatures
packaging	200 Kg Drums en 1.000 Kg IBC-Container
removal	according to local/regional/national regulations
Shelf life	12 months after production date at +5° C to +30° C

PDS INCRASURF V60 EN 05-2018

Ingwio BV | Niersenseweg 25 | NL-8076 PW Vierhouten  
T: +31 577 411 168 | E: info@in-cra.com | I: www.incra.nl

INCRA is a registered trademark of Ingwio BV. All rights reserved.

All information in this product data sheet is conform the current state of development and knowledge of Ingwio BV. It serves only as a guideline for the processing, uses and properties of the product. There can be no legal obligations deduced from this with respect to the properties of this product. Above that our current terms are applicable. Changes reserved.